SUMMIT

UMBROSA UMBRELLA FABRICS

COLORUM & SOLIDUM

SUMMIT

CHARACTERISTICS	VALUES		UNITS	STANDARDS
	WARP	WEFT		

OVERALL CHARACTERISTICS

Composition	100% solution dyed acrylic	100% solution dyed acrylic			
Finish	Stain-resistant treatment: Exclusi	Stain-resistant treatment: Exclusive Glen Raven formulation.			
	Does not contain PFOS (perfluor	Does not contain PFOS (perfluoroctanyl sulphonate)			
Weave	Weave	Weave ISO 7211-1			
Mainht	260	g/m²	150 2001		
Weight	6.17	lb/ft	ISO 3801		
Width	137	cm	EN 1770		
	53.94"	53.94" EN 1773			

FABRIC STRENGTH

Tensile strength	160	80	daN	ISO 13934-1
Tear strength	7	3.7	daN	ISO 13937-1

COLOR RESISTANCE

Color fastness UV	7/8	class/8	ISO 105 B02
Color fastness weather condition	7/8	class/8	ISO 105 B04

USE

Roll length	50	Im
	164	lf
Recommended use	parasols, cushions, upholstery	
Guarantee	3	Years
Temperature of use	-20 >> +70	°C
	-4 >>+158	°F

COLORS



Monitor/printer colors may vary. Please refer to actual fabric before making your final decision.

The content of this document, in particular the mentioned models, is protected by copyrights and/or design rights. The present document and its content is communicated to you for information purposes only. Any partial or total reproduction or any other use without our prior written permission is strictly prohibited. This technical sheet remains subject to possible changes. Of course we do our best to eliminate all mistakes, but Umbrosa is not responsible for the errors in the documentation of products. All measurements are approximate and are provided for informational purposes only.

SUMMIT

CHARACTERISTICS	VALUES		UNITS	STANDARDS
	WARP	WEFT		

OVERALL CHARACTERISTICS

Composition	100% solution dyed acrylic	100% solution dyed acrylic		
Finish	Stain-resistant treatment: Exclusive Gler	Stain-resistant treatment: Exclusive Glen Raven formulation.		
	Does not contain PFOS (perfluoroctanyl	Does not contain PFOS (perfluoroctanyl sulphonate)		
Weave	Weave	Weave		
	255	g/m²	100 0001	
Weight	6.05	lb/ft	ISO 3801	
NA2 111	137	cm	EN 1770	
Width	53.94	inch	EN 1773	

FABRIC STRENGTH

Tensile strength	160	80	daN	ISO 13934-1
Tear strength	7	3.7	daN	ISO 13937-1

COLOR RESISTANCE

Color fastness UV	7/8	class/8	ISO 105 B02
Color fastness weather condition	7/8	class/8	ISO 105 B04

USE

Roll length	50	Im
	164	lf
Recommended use	parasols, cushions, upholstery	
Guarantee	3	Years
Temperature of use	-20 >> +70	°C
	-4 >> +158	°F

COLORS



Monitor/printer colors may vary. Please refer to actual fabric before making your final decision.



The content of this document, in particular the mentioned models, is protected by copyrights and/or design rights. The present document and its content is communicated to you for information purposes only. Any partial or total reproduction or any other use without our prior written permission is strictly prohibited. This technical sheet remains subject to possible changes. Of course we do our best to eliminate all mistakes, but Umbrosa is not responsible for the errors in the documentation of products. All measurements are approximate and are provided for informational purposes only.